

Antenna-Roof-2W

Dachantenne mit MIMO WLAN

Omnidirektionale Kombiantenne mit linearer Polarisisation zur Signalverbesserung in WLAN-Netzwerken.

Hauptmerkmale

WiFi / WLAN	MIMO 2.4 / 5 GHz
Vehicle	ECE R118



Spezifikation

WiFi / WLAN	Standards	2 x Dual-band WLAN 2.4/5 GHz
	Frequency (MHz)	2408 - 2480, 5150 - 5850
	Gain	3 dBi (WLAN 2.4) / 1 dBi (WLAN 5)
	VSWR	≤ 2 typ.
	Impedance	50 Ohm
	Radiation	omnidirectional
	Connectors	2x SMA male fix connected 3m antenna cable
Mechanical	Dimensions	Diameter 76 mm
		Height 21 mm
	Weight	160 g
	Mounting	Rooftop with screws no ground plane needed
	Color	black
	Operating Temperature	-40°C bis +85°C
	Ingress Protection Level	IP69K - Staubdicht, Schutz gegen Wasser bei Hochdruck-/Dampfstrahlreinigung
Certifications	Compliance	RoHS, REACH
	Domain	Industrial
Extension Cables	WLAN	2 x fix connected / 3 m / SMA male
Other	Order Code	Antenna-Roof-2W