

Antenna-Coach-2L

Coach Roof Antenna with MIMO LTE + UN ECE R118

Omnidirectional combo antenna for signal enhancement in 4G, 3G, 2G networks.



Keyfeatures

Cellular	MIMO LTE / UMTS / GSM
Vehicle	UN ECE R118

Specifications

Mobile / Cellular	Standard	2 x LTE / UMTS / GSM LTE Bands: 1, 2, 3, 4, 5, 7, 8, 10, 11, 12, 13, 14, 17, 18, 19, 20, 21, 23, 24, 25, 26, 27, 28, 29, 30, 32, 65, 66, 67, 68, 69, 70, 74, 75, 76, 85 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 45, 50, 51, 53 UMTS Bands: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 19, 20, 21, 25, 26, 32 - TDD Bands: 33, 34, 35, 36, 37, 38, 39, 40 GSM Bands: 700, 850, 900, 1800, 1900 Frequency 700 - 2600
	Specification	Gain -9 dBi typ. (700 MHz) ±0 dBi typ. (800 MHz) +3 dBi typ. (900 MHz) +3 dBi typ. (1800 MHz) +1 dBi typ. (2100 MHz/UMTS) +2 dBi typ. (2600 MHz) VSWR ≤ 2 typ. Impedance 50 Ohm Radiation omnidirectional
	Connectors	2x FAKRA D-coded female fix connected 3m antenna cable
Mechanical	Dimensions	Diameter 112 mm Height 30 mm
	Weight	350 g
	Mounting	Rooftop with screws no ground plane needed
	Color	black
Environment	Operating Temperature	-40°C to +85°C
	Ingress Protection Level	IP69K - Dust-tight, protected against close-range high pressure, high temperature spray downs
Certifications	Compliance Domain	RoHS, REACH, Vehicle according to UN ECE R118 Vehicle
Extension Cables	Cellular	2 x fix connected / 3 m / FAKRA D-coded female
Other	Order Code	Antenna-Coach-2L