

NB3800-NWac2D2CmDb-Glx

Railway Router with LTE + 2x WLAN-ac 5x ETH + CAN-passive + IBIS + GNSS + FMS2IP + ITxPT + EN50155

Railway approved, modular onboard communication platform for future proof IP solutions.



Keyfeatures

Mobile / Cellular	1x LTE, UMTS, GSM
SIM	4x Mini SIM
WiFi / WLAN	2x Dual Band IEEE 802.11a/b/g/n/ac (Wi-Fi 5), 100 Clients in Access Point Mode
Ethernet	2x Gigabit Ethernet, 3x Fast Ethernet
Serial / Fieldbus	1x CAN passive (read only) with FMS to IP Gateway, 1x IBIS
Power	24 VDC to 48 VDC
Positioning	Multi-GNSS
Temperature Range	-40 °C to +70 °C, EN 50155 class OT4/ST0
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, FMS2IP, free updates
Compliance	CE (RED), Railway (EN50155, EN45545), ITxPT
Modularity	Extensions on request

Product description

The NB3800, with its railway approvals and ITxPT compliance and its interfaces to on-board electronics, is the ideal device for e.g. WLAN and passenger information or production data acquisition.

Applications

- Passenger WiFi
- Passenger Infotainment
- Smart Traffic
- Telematics
- CCTV

Specifications

Mobile / Cellular	Standard	1x Multimode 5G-NR, LTE-A Pro, UMTS 5G - NR n1, n2, n3, n5, n7, n8, n12*, n20, n25, n28, n38, n40, n41, n48, n66, n71, n77, n78, n79 2014/53/EU (RED): n1, n3, n7, n8, n20, n28, n38, n40, n77, n78 4G - LTE-A Pro B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29DL, B30, B32, B34, B38, B39, B40, B41, B42, B43*, B46(LAA), B48(CRS), B66, B71 2014/53/EU (RED): B1, B3, B7, B8, B20, B28, B38, B40 3G - DC-HSPA+/UMTS B1, B2, B3, B4, B5, B6, B8, B9, B19 2014/53/EU (RED): B1 (2100), B3 (1800), B8 (900) 5G NR Modes Sub-6 FDD and TDD LTE Category Cat. 20 up to 7CA MIMO 4x4 MIMO in 5G-NR support on n1, n2 n3, n7, n25, n38, n40, n41, n48, n66, n77, n78, n79 and LTE B1, B2, B3, B4, B7, B25, B30, B38, B39, B40, B41, B42, B43, B46, B48, B66 Antenna ports 4 Power Class 23dBm (Power Class 3) Data rate down / up (max) up to 5.5 Gbps DL / 2.7 Gbps UL Operation Mode 5G Core SA and NSA operations 3GPP 4G/5G Rel. 15, 3G HSPA+ Rel. 18 FCC ID RI7FN980 Voice - Region Europe, Middle East and Africa (EMEA), North America (NA), Asia and Pacific (APAC) * future Module Firmware release
	Region	Europe, Middle East and Africa (EMEA)
	Connectors	2x TNC female
	SIM	4x Mini SIM - 2FF

WiFi / WLAN	Standard	1x WLAN 2.4/5 GHz a/b/g/n/ac (Wi-Fi 5) Wireless standard IEEE 802.11a/b/g/n/ac (Wi-Fi 5) Frequency 2.4/5 GHz Diversity 2x2 MIMO Data rate (max) 300 Mbps (2.4 GHz) / 866 Mbps (5 GHz) Modes Client or access point (up to 100 clients) FCC ID TK4WLE600VX
	Connector	4x TNC female
Ethernet	Standard	2x Gigabit Ethernet Ethernet standard 1000BASE-T, Auto MDIX Speed 10/100/1000 Mbps 3x Fast Ethernet Ethernet standard 100BASE-TX, Auto MDIX Speed 10/100 Mbps
	Connector	2x M12 X-coded female, 3x M12 D-coded female
Positioning	Standard	1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS/QZSS 72-channel u-blox M8 engine 3 concurrent GNSS channels Antennas Active or passive Accuracy Up to 2.5 m CEP Sensitivity Up to -167 dBm Services Standalone, Assisted GPS Data server with JSON, NMEA data stream
	Connector	1x TNC female
USB	Standard	1x USB 2.0 Host
	Connector	1x Type A
Serial, Fieldbus	Protocol	1x CAN Protocol Controller Area Network V2.0B (ISO 11898) Signals CANH, CANL Signal level High > 2.75 V, low < 2.0 V Frames/s Up to 8000 Frames/s Isolation 1500 VDC Termination No internal bus termination Bus access Passive - read access only Optional: Active - read and write access on request (Productoption-2Cn) 1x RS-232/485 combo (software switchable) Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 115'200 Bit/s Protocol EIA-485 Signals A, B Signal level Differential output voltage, loaded 1.5 VDC - 3.6 VDC Bit rate Up to 115'200 Bit/s Termination 120 Ω for RS-485 configurable by software
	Connector	1x M12 A-coded female
IOs	Type	1x Digital I/O Signals 2x DI, 2x DO DI signals +, - DI level Low: 0 - 5 VDC, high 9 - 60 VDC DI isolation 1'500 VDC DO level 0 - 60 VDC/1A DO signals Relay outputs with NO, NC, COM (normally open, normally closed) DO isolation 1'500 VDC
	Connector	1x M12 A-coded female
Extended Storage		64 GB SSD Capacity 64 GB Technology SSD Data Application data such as logs, media content, ...
System	Core	1.3 GHz dual-core, 1 GB RAM, 4 GB flash
	Module Slots	2x miniPCIe (PCIe + USB), 4x miniPCIe (USB)

Software	Features	NetModule Router Software (supported features depending on product variant) Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license) Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision, Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports) Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography) Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow) Programmability SDK Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test
	Licenses	GNSS, Enabled service GNSS location service Server with JSON-, NMEA stream ITxPT Enabled services Inventory, Time, FMS2IP (requires -F option), Vehicle2IP (requires -F option), Location (requires -G option) Standard ITxPT software compliance
Power	Input Voltage	24, 48 VDC Nominal voltages 24, 48 VDC Absolute voltages 24 VDC to 48 VDC (–30 % / +30 %) Galvanic isolation 1500 VDC Standard EN 50155 class S2/C1
	Connector Consumption	1x M12 A-coded male 25 W (max)
Dimensions	W x H x D	Width 167/190 mm x height 121.1 mm x depth 106.5 mm
Weight		2000 g
Environment	Operating Temperature	–40°C to +70°C
	Ingress Protection Level	IP40
MTBF		148'000 h / 16.9 years, according SN29500 at environmental temperature 40 °C
Certifications	Compliance	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), Railway according to EN 50155 class OT4/ST0, EN 45545, ITxPT (Hardware compliance requires adapter cables), Automotive according UN ECE R10 (e-Mark), UN ECE R118
	Domain	Railway
Order Code		NB3800-NWac2D2CmDb-Glx