

NB3701-LbbWac-G

Bahn-Router mit LTE-NA + WLAN-ac + 5x ETH + GNSS + EN50155

Modularer Mobilfunk-Router mit 5-Port Ethernet Switch für drahtlosen Internetzugang im Fahrzeug.



Hauptmerkmale

Mobilfunk	1x LTE, UMTS, GSM für NA
SIM	2x Mini SIM
WiFi / WLAN	1x Dual Band IEEE 802.11a/b/g/n/ac (Wi-Fi 5), 100 Clients im Access Point Mode
Ethernet	5x Fast Ethernet
IO	4x Digitale I/O
Speisung	24 VDC bis 48 VDC
Ortung	Multi-GNSS
Betriebstemperatur	-40 °C bis +70 °C, EN 50155 class OT4/ST0
Software	Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, freie Updates
Konformität	CE (RED), Bahn (EN50155, EN45545)
Modularität	Erweiterungen auf Anfrage

Produktbeschreibung

Der NB3701 ist der kompakte Router für die Bahn und andere Einsatzgebiete, wo ähnliche Anforderungen an die Hardware bestehen. Er ist das passende Gerät für Anwendungen wie Mining oder Passagier-WLAN.

Anwendungen

- Intelligenter Verkehr
- Mining
- Passagier-WLAN
- Passagier-Infotainment
- Videoüberwachung

Spezifikation

Mobile / Cellular	Standard	1x Multimode LTE, UMTS, GSM for NA 4G - LTE B2 (1900), B4 (1700), B5 (850), B7 (2600), B17 (700) 3G - DC-HSPA+/UMTS B1 (2100), B2 (1900), B4 (AWS), B5 (850), B8 (900) 2G - GSM/GPRS/EDGE B2 (1900), B3 (1800), B5 (850), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB FCC ID XPTYOBYL200
	Region	North America (NA)
	Connectors	2x TNC female
	SIM	2x Mini SIM - 2FF
WiFi / WLAN	Standard	1x WLAN 2.4/5 GHz a/b/g/n/ac (Wi-Fi 5) Wireless standard IEEE 802.11a/b/g/n/ac (Wi-Fi 5) Frequency 2.4/5 GHz Diversity 2x2 MIMO Data rate (max) 300 Mbps (2.4 GHz) / 866 Mbps (5 GHz) Modes Client or access point (up to 100 clients) FCC ID TK4WLE600VX
	Connector	2x TNC female
Ethernet	Standard	5x Fast Ethernet Ethernet standard 100BASE-TX, Auto MDIX Speed 10/100 Mbps
	Connector	5x M12 D-coded female

Positioning	Standard	<p>1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS/QZSS 72-channel u-blox M8 engine 3 concurrent GNSS channels Antennas Active or passive Accuracy Up to 2.5 m CEP Sensitivity Up to -167 dBm Services Standalone, Assisted GPS Data server with JSON, NMEA data stream</p>
	Connector	1x TNC female
USB	Standard	1x USB 2.0 Host
	Connector	1x Type A
IOs	Type	<p>4x Digital I/O Signals 2x DI, 2x DO DI signals +, - DI level Low: 0 - 5 VDC, high: 7.2 - 40 VDC DO signals Relay outputs with NO, NC, COM (normally open, normally closed) DO level 0 - 60 VDC/1A, maximum switching capacity: 60 W Isolation 1'500 VDC</p>
	Connector	1x M12 A-coded female
System	Core	1.3 GHz dual core, 1 GB RAM, 4 GB flash
	Module Slots	2x miniPCIe (PCIe + USB)
Software	Features	<p>NetModule Router Software Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license) Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision, Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLD, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, LZTP, CSD dial-in, Certificate revocation service Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports) Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography) Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow) Programmability SDK Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test</p>
	Licenses	<p>GNSS/GPS Services Server with JSON-, NMEA stream</p>
Power	Input Voltage	<p>24, 48 VDC Nominal voltages 24, 48 VDC Absolute voltages 24 VDC to 48 VDC (-30 % / +30 %) Galvanic isolation 1500 VDC Standard EN 50155 class S2/C1</p>
	Connector Consumption	<p>1x M12 A-coded male 15 W (max)</p>
Mounting		Bracket
Dimensions	W x H x D	Width 165/190 mm x height 85 mm x depth 104 mm
Weight		1100 g

Environment	Operating Temperature Ingress Protection Level	-40°C to +70°C IP40
MTBF		210'000 h / 24 years, according SN29500 at environmental temperature 40 °C
Certifications	Compliance Domain	CE according to 2014/53/EU (RED), 2011/65/EU (RoHS), Railway according to EN 50155 class OT4/ST0, EN 45545 Railway
Order Code		NB3701-LbbWac-G