

NB1800 Industrial Router

High-Performance Wireless Router with LTE Advanced Pro, WLAN, Gigabit Ethernet, SFP, Serial Interfaces and GNSS

16.06.2023, ©NetModule AG
Product Information NB1800
Errors reserved



Key Features

| | |
|--------------------------|-----------------------------------------------------------------------------------------------|
| Mobile / Cellular | 1 - 2x LTE Advanced Pro, UMTS |
| SIM | 2x Micro SIM |
| WiFi / WLAN | 1 - 2x Dual-band IEEE 802.11ac (Wi-Fi 5) |
| Ethernet | 2x Gigabit Ethernet, 1x SFP |
| Extended Storage | 1x SD Card |
| Serial / Fieldbus | 1x RS-232/485 |
| Positioning | Multi-GNSS |
| Temperature | -40 °C to +70 °C |
| Software | Routing, Network Services, VPN, Firewall, Link Management, Supervisor, LXC, SDK, free updates |
| Compliance | CE (RED), UKCA (RER) |
| Modularity | Extensions on request |

Product Description

The powerful NB1800 router enables fast Internet access in an industrial environment. For a reliable network connection, the device supports multiple cellular modules as well as WiFi modules according to the latest IEEE 802.11ac (Wi-Fi 5) standard. Also included are two Gigabit Ethernet and a SFP port (typ. used for fiber optic), as well as a USB host port and a serial interface with RS-232 or RS-485 mode.

DIN rail mounting, the wide operating temperature range from -40 °C to 70 °C and the IP40 metal housing allow reliable operation under harsh conditions. Combined with its versatile features and performance, this makes the NB1800 ideal for applications such as Industrial Security, CCTV or Point of Sale Connectivity.

The software is based on well proven components including an embedded Linux operating system and a powerful communication protocol suite as well as VPN technologies as OpenVPN. Customer specific software extensions may be implemented via a sophisticated SDK.

Applications

- Industrial Security
- Point of Sale
- Public WiFi
- CCTV
- Smart Grid
- Factory Automation

Specifications

1 - 2x Mobile / Cellular (optional) Multimode LTE, UMTS and GSM

4G - LTE

B1, B3, B7, B8, B20, B28

3G - DC-HSPA+/UMTS

B1, B3, B8

2G - GSM/GPRS/EDGE

B3, B8

LTE Specification

LTE Cat 4, 2x2 MIMO

DL 150 Mbps / UL 50 Mbps

Voice

CSFB, VoLTE (with optional License)

Region

EMEA

OR

1 x Mobile / Cellular (optional) Multimode LTE Advanced Pro, UMTS

4G - LTE

B1, B3, B7, B8, B20, B28, B38, B40

3G - DC-HSPA+/UMTS

B1, B8

LTE Specification

LTE Cat 12, 2x2 MIMO

DL 600 Mbps / UL 150 Mbps

Region

EMEA (APAC or NA on request)

Connector

2 - 4x SMA female

SIM

2x Micro SIM - 3FF

1 - 2x WiFi / WLAN (optional)

Standard

IEEE 802.11a/b/g/n/ac (Wi-Fi 5)

Dual-band 2.4/5 GHz

2x2 MIMO

Bit rate (max)

144 Mbps 2.4 GHz, 150 Mbps 5 GHz

Modes

Client or Access Point (max. 100 Clients)

Connector

2-4x SMA female

3x Ethernet

2x Gigabit Ethernet

1x SFP / GbE combo

Standard

1000Base-T, Auto MDIX

Speed

10 / 100 / 1000 Mbps

Connector

2x RJ45

1x SFP Cage (mini GBIC)

USB

1x USB 2.0 Host Port

Connector

1x Type A

Positioning (optional)

GNSS Receiver (depending on model)

BeiDou, Galileo, GLONASS, GPS/QZSS

Sensitivity

Up to -167 dBm, up to 2.5m CEP

Antennas

Active or passive

Connector

1x SMA female

1x Serial, Fieldbus

Protocol

RS-232/485 combo (software switchable)

Signals

A, B / TX, RX

Bit rate

Up to 115 200 Bit/s

Termination

120 Ω for RS-485 configurable by software

Connector

1x Terminal block header 3.5 mm (screw locking)

1 - 2x Module Options

Options

Customer specific, please contact us

Connector

Module specific

System

Core

1.3 GHz dual core, 1 GB RAM, 4 GB flash

Extended Storage

1x SD Card Slot

Power

Nominal Input voltages

12, 24, 48 VDC (-25 % / +10 %)

Average Power Consumption

11 W

Maximal Power Consumption

20 W

Connector

1x Terminal block header 3.5 mm (screw locking)

Other

Mounting

DIN-Rail

Dimensions

Width 61 mm x height 128/140 mm x depth 121 mm

Weight

ca. 800 g

Environment

Operating Temperature

-40 °C to +70 °C

Ingress Protection Level

IP40

MTBF

240'000 h / 27.4 years, according SN29500 at environmental temperature 40 °C

Software

Features

Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates

Licenses (optional)

Voice Gateway, LXC Virtualization, OpenVPN- and DynDNS Server, GNSS, Enhanced RF Configuration

Certifications

Compliance

CE according to 2014/53/EU (RED), UKCA according to Radio Equipment Regulations 2017 No. 1206 (RER), 2011/65/EU (RoHS)

Ordering options

Contact our sales team for our standard models, options or project specific adaptations